# **Key Features List**

# 23,6" LCD FHD DVB-T/C MPEG4 TV DVD

Model: SZTV-246FDGW5

Main board: MSD308

#### PICTURE:



# **BRIEF:**

- CCFL FHD LCD panel
- Slim cabinet design (designed by Ed-Design, Finland)
- Sensor touch pad front keyboard
- ATV and DVB-T/C
- MPEG4 decoding
- CI Common Interface
- Media Player (photo, music, video)
- PVR/TSR functionality
- 2xHDMI, 1xUSB connectors
- 2x10W powerful sound (2%THD)
- Wall mounting 100x100mm by VESA standard

# **CABINET:**

Type: INNO 61Front cabinet: glass

Back cabinet: plastic ordinary black Stand: plastic UV black Connectors: on the cabinet sideThickness: 42mm

• Thickness: 42mm

#### **PANEL:**

Panel resolution: 1920 x 1080 pixels (16:9);

 Response time: 3.5 ms; Brightness: 300 nit;Contrast ratio: 1000:1

Viewing angle: 178(H)/170(V);

Colors: 16.7 M

#### **ANALOG TV FUNCTIONS:**

- Analog hyperband terrestrial TV Tuner (PLL) E2 S6(VHF-L), S7 S41(VHF-H), E21 - E69(UHF), bandwidth: from 49 to 863 MHz.
- TV Standard PAL / SECAM color system receiving
- Auto color system detection
- BG / DK / I / L and NICAM / A2 STEREO sound system receiving
- Automatic sound system recognition
- TV Standard in video mode PAL / SECAM color system receiving
- 100 program memory
- DNR (Dynamic Noise Reduction )
- 3D Comb Filter
- 3D de-interlacing
- Picture adjustment
- Manual channel tuning
- Manual program labeling
- Automatic channel tuning and store
- Manual programs sorting
- Auto standby mode after 5 minutes, while no input signal
- Picture zoom: 4:3, 16:9, ZOOM1, ZOOM2
- Picture mode selection
- Volume and Balance control
- Sound mode selection
- OSD (on screen display) high performance
- Sleep timer
- Blue screen function when no signal
- Full function remote control hand-unit
- Teletext 750 pages
- YPbPr formats: 480i, 576i, 1080i, 480p, 576p, 720p, 1080p
- HDMI 1.3 formats: 480i, 576i, 1080i, 480p, 576p, 720p, 1080p
- VGA max resolution 1920X1080@60Hz
- Power voltage 220VAC (12VDC optionally)

#### **DIGITAL TV FUNCTIONS:**

DVB-T/C functions:

DVB standard: EN 300 744

o FEC: Reed-Solomon 1/2, 2/3, 3/4, 5/6, 7/8 COFDM QPSK, 16QAM, 64QAM Modulation:

o FFT size: 2k, 8k;

o Guard interval: 1/32, 1/16, 1/8, 1/4

- DVB definition:
  - o SD 576p
- DVB FTA TV reception;
- DVB FTA Radio reception;
- Video decoding:
  - o MPEG-2 MP@ML
  - o MPEG-4 H.264
- Audio decoding:
  - o MPEG-1/MPEG-2 layers 1, 2
- CA (Conditional Access) functions:
  - CI (Common Interface)
  - DVB scrambled TV reception (with external CI CAM module);
  - DVB scrambled Radio reception (with external CI CAM module);
- EPG 7days;
- · Real time clock EPG timer;
- Country setting;
- Subtitles;
- LCN (Logical Channel Number);
- DVB Teletext (optional);
- MHEG-5 (optional).

# **DVD FUNCTIONS:**

- Compatibility of Disc:
  - o CD, VCD, SVCD
  - DVD, DVD+R, DVD-R, DVD+RW, DVD+RW
- Multimedia formats:
  - o Photo (JPG, JPEG)
  - Music (MP3, WMA)
  - Video (MPEG1, MPEG2, AVI);

#### **MEDIA FUNCTIONS:**

- USB Media player:
  - o Photo (JPG, JPEG)
  - Music (MP3, WMA)
  - Video (MPEG1, MPEG2, AVI);
- USB PVR
  - Manual program recording
  - Program recording by EPG timer
  - TSR (Time Shift Recording)
- USB storage device:
  - Flash memory stick
  - o HDD
- USB SW update

#### **INPUT/OUTPUTS:**

HDMI1.3: 2x connectorsUSB2.0: 1x connector

VGA video input: 1x 15D-SUB connectors

VGA audio input: 1x 3.5mm mini-jack connector

CI: 1x PCMCAI connector

AV audio/video input: 1x 3.5mm mini-jack connector
 YPrPb (component) input: 1x 3.5mm mini-jack connector
 HP (Headphones): 1x 3.5mm mini-jack connector

RF aerial input: 1x connectorSCART 1x connector

12VDC 1xconnector for external 12V power

# **LOCAL CONTROL:**

Front sensor (touchpad) keyboard:

 9 keys: PLAY/PAUSE, EJECT, SOURCE, CH-, CH+, VOL-, VOL+, MENU, POWER

- 220VAC power switch
- Full-function IR remote control

#### **POWER SAVINGS:**

Power consumption in standby mode: <1W</li>
 Power consumption in power off mode: 0 W

Auto standby, while no signal within: 5 minutes
Max power consumption: 60 W

# **OSD LANGUAGES:**

Norwegian Spanish Bulgarian French Croatian German Polish Swedish Czech Greek Portuguese Dutch Romanian Danish Hungarian Serbian Italian English Russian Russian

EstonianFinnishLatvianSlovakianSlovenian

#### **QUALITY PARAMETERS:**

Approved certificates: EMC, EMI, LVD, RoHS, PAH, VDE

Approved standards: DVB, Nordig2.0, DTG

# **DIMENSIONS:**

• Thickness: 42,2 mm

Max dimensions: 580 x 42,2 x 370 mm (without stand)
Max dimensions: 580 x 180 x 400 mm (with stand)

#### **NET WEIGHT:**

• 6,8 kg